



Breaking Ground, Building Trust.

Casing Rotator Operation



20" Casing Shoe



Tooling

Preferred Straight Rig Stabilizer

12" Hammer and 18-1/2" Bit for 20" Casing



Loaded Casing

Forklift is used to feed drill pipe into casing before loading on pipe system





Breaking Ground, Building Trust.™

Prepare for Next Connection

Install Dog Collar to secure casing



Disconnecting Diverter with Air Wrench



Engaged Diverter Retainer

Raise tophead to align drill string with holding wrench





Breaking Ground, Building Trust.™

Engage Hydraulic Wrench

Break connection with tophead





Breaking Ground, Building Trust.™

Pick Up Process

Tilt tophead to align with loading system





Breaking Ground, Building Trust.

Pick Up Continued



Thread Connection

Insure that tool joint is mated before lifting



Engage Diverter

Be sure that casing is fully seated before anchor connections are made



Install Retainer Tab

Tab will insure that casing is secure during lifting operations



Weld Retainer Tabs





Breaking Ground, Building Trust.™

Pick Up Connection





Breaking Ground, Building Trust.™

Pick Up Continued





Breaking Ground, Building Trust.™

Align Drill Pipe Connection





Breaking Ground, Building Trust.™

Make Connection





Breaking Ground, Building Trust.™

Retract Holding Wrench





Breaking Ground, Building Trust.™

Align & Weld Casing





Breaking Ground, Building Trust.™

Drilling Casing Rotated CCW



Air and Cutting Diverted to Cyclone



Breakout on Swing Arm Required When Tripping Out





Breaking Ground, Building Trust.

Thank You

